ENVIRO CARENovus Floor Finish



Environmental & Safety Benefits

- Neutral pH
- Readily Biodegradable*
- No Suspected Endocrine Disruptors
- No Heavy Metal Complexes, APE's, Formaldehyde
- No Odor
- Non-Corrosive
- Non-Reactive
- Phthalate Free

Directions for Use

Floor preparation: For best results, start with a properly prepared floor by removing all of the old finish using Enviro Care Floor Stripper according to its directions. Rinse floor thoroughly to remove all residues and allow to dry.

Application:

Do not apply product if flooring and/or ambient temperatures are less than 55°F (13°C).

- 1. If not sealed, build an adequate base for ease of maintenance with the desired floor care system by applying three (3) thin coats of Enviro Care Novus. Allow adequate drying time between coats, typically 75°F (24°C) and 50% relative humidity requires an average of 45 minutes. Adjust drying times according to specific application conditions.
- 2. For added depth of gloss and protection, apply an additional two (2) thin coats may be applied. If applying thick coats allow 24-48 hours dry time before applying.

Maintenance

Enviro Care Novus is an environmentally preferable zinc-free coating that may be attacked or dulled by harsh cleaners.

- 1. Daily dust mopping or sweeping will remove abrasive debris that will impact appearance and increase maintenance.
- 2. Damp mop or autoscrub using 1/2 oz per gallon of Enviro Care Low Foam All Purpose Cleaner.
- 3. Recommend using aqua pad with burnishing machine, for gloss restoration.
- 4. Deep-scrub as required to maintain finish and gloss.

Coverage: Up to 3000 square feet per gallon.

Slip Resistance: Meets ASTM D2047-93 requirements for slip resistance.

Product Performance Characteristics

Enviro Care Novus creates a new standard in floor care by combining an unequaled level of environmental preference with performance, which surpasses conventional floor finish technology.

Enviro Care Novus excels with all maintenance systems: scrub and recoat, spray buff or burnish. You'll get a tough, black-mark resistant shine with no powdering. No sealer is required on resilient flooring, even after heavy stripping.

Properties

8.3-8.6
8.3-8.6 1.03
white
79
excellent excellent
excellent
<1%
Up to 3000 sq ft/gal.

Health and Hazard Ratings

Category	NFPA	HMIS
Health	1	1
Fire	0	0
Reactivity	0	0
Protective Equipment	None	В

For handling and precautionary information, reference the product label and material safety data sheet.

Ordering Information

FXENVROCARENOVUS 2.5 Gallon (2/cs)

For more information call 800-670-4537 or go to www.iaprisonind.com.



www.rochestermidland.com



This product meets EcoLogo™ Environmental Standard for Hard Floor Care Products (CCD-147) based on its low impact for human and environmental health

* As defined in 40CFR796.3200 EPA/TSCA

All data statements and information presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, express warranty or implied warranty or merchantability or fitness for a particular purpose, or representation, express or implied, for which seller assumes legal responsibility, and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent. Printed in USA. Copyright © 2011 Rochester Midland Corporation.